

This 134.2 kHz low frequency RFID ear tag is specially designed for animal management.

This 134.2 kHz low frequency RFID ear tag is specially designed for animal management and is commonly used for tagging sheep, goats or other similar kinds of animals. It is compliant with ISO 11784/5 FDX-B standard. This tag features a compact size, light weight and high anti-collision capability. It has a lifespan of more than five years.



Key Features

- ✓ Compact size and light weight
- ✓ ISO11784/5 HDX-B compliant
- ✓ High anti-collision

Technical Specifications

Operating Frequency	134.2 kHz
Chips	Hi tags, EM tags
Color	Yellow or Pink
Max Tension	300 N
Anti-collision	IEC 68-2-27
Shaking	IEC 68-2-6
Supported Protocol	ISO 11784/5 FDX-B
Dimensions	118 mm * 16.5 mm * 13.3 mm ± 0.3 mm
Material	Thermoplastic Polyurethane
Life Span	>5 years
Operating Temperature	-30 °C to 85 °C
Certification	ICAR

<p>GAO Group</p> <p>GAORFID.com</p> <p>GAOTek.com</p> <p>GAOResearch.com</p>	<p>Toll Free (USA & Canada)</p> <p>1-877-585-9555</p> <p>All Other Areas</p> <p>416-292-0038</p> <p>Dial Ext.601 for Sales Ext.602 for Other Inquiries</p> <p>sales@GAORFID.com</p>
---	---