

This UHF RFID zip tie tag is specially with internal metal wire to make it difficult to remove the tag from any asset.

This UHF RFID zip tie tag is specially designed with internal metal wire to make it difficult to remove the tag from any asset. It is often used for logistics and food or animal traceability applications.



Key Features

- ✓ Waterproof, anti-corrosion, durable
- ✓ Anti-collision algorithm
- ✓ Durable lock
- ✓ Provides reliable read

Technical Specifications

Material	PP	
Dimension	Label dimension	53.5mm×30mm×3.1mm
	Tie rod length	277.5mm×7.6mm×1.9mm
	Total length	320mm
Chip	G2XM (Other UHF chips customizable)	
Operating frequency	915MHz (ISO/IEC 18000-6C)	
Operating Temperature	-30 °C to 85 °C	
Read range	3-4m, handheld reader read range of 0.22 to 0.24m; read range dependent on reader	
Pull	430 to 460 N	
Lock force	210 to 215 N	

<p>GAO Group</p> <p>GAORFID.com</p> <p>GAOTek.com</p> <p>GAOResearch.com</p>	<p>Toll Free (USA & Canada)</p> <p>1-877-585-9555</p> <p>All Other Areas</p> <p>416-292-0038</p> <p>Dial Ext.601 for Sales Ext.602 for Other Inquiries</p> <p>sales@GAORFID.com</p>
---	---