

This low frequency handheld RFID animal reader provides a low cost contactless system for animal identification and management.

This low frequency handheld RFID animal reader provides a low cost contactless system for animal identification and management. It features high performance, a user-friendly sleek design and is well suited for stock breeding, animal control or foodstuff tracking systems. The one button operation makes it easy to use and enables any professional veterinarian and non-professional alike to use it to read the electronic data on any pet equipped with an electronic RFID chip. The low frequency RFID livestock reader is compliant with ISO11784/11785 FDX-B standard and is able to read tags from a distance of up to 120 mm. It is shipped with a FSTN screen and allows for clear view of data.



Technical Specifications

Frequency	134.2 kHz
Protocol format	FDX-B
Standard	ISO11784/11785
Reading distance	Up to 120mm (30 mm Electronic ear tag) Up to 75 mm (2.12 mm × 12 mm Glass tube)
Interface	USB (RS232 Optional)
Power supply	9-volt alkaline battery
Dimensions	147 mm × 45 mm × 22mm
Weight	68 g (not including battery)



GAO Group

GAORFID.com
GAOTek.com
GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales
Ext.602 for Other Inquiries

sales@GAORFID.com